



MLFB-Ordering data:

1LE7501-1BB23-5FA4-Z  
F07+F14+H23+R50

Frame size: 112M

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]±10%	Δ/Y [Hz]±5%	f [Hz]±5%	P [kW]	I [A]	n [1/min]	M [kgf.m]	M [Nm]	NOM. EFF at ... load [%] *			Power factor at ... load *			I <sub>A</sub> /I <sub>N</sub> I/I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>A</sub> /T <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
415	Δ	50	3.70	7.40	1445	2.5	24.4	86.3	86.3	86.0	0.81	0.74	0.61	6.5	2.6	2.9	IE2

Data subject to tolerance as per IS 12615 / IEC 60034-1

SF: 1.00

\*sinusoidal feed

Environmental conditions : -20 °C to +50 °C / 1000.0 m

locked rotor withstand time (hot / cold) : 8.0 s / 10.0 s

Mechanical data		Terminal box	
Sound pressure level 50Hz   60Hz	64 dB(A)	67 dB(A)	Terminal box position
Type of construction	IM B5 / IM 3001	Material of terminal box	Aluminium
Bearing DE   NDE	6206 2ZC3	Type of terminal box	TB1 F14
Type of bearing	Locating (fixed) bearing, NDE	Contact screw thread	M5
Lubricants	Esso Unirex N3	Max. cross-sectional area	16.0 mm <sup>2</sup>
Regreasing device	- / -	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Grease nipple	- / -	Cable entry	2xM32x1,5+1xM20x1,5
Bearing lifetime	50000 h	Cable gland	2 Plugs
Degree of protection	IP55	Special design	
External earthing terminal	Yes (standard)	F07	Mounting a brake
Vibration severity grade	A (Standard)	F14	Brake supply voltage 415 V AC, 50/60 Hz
Insulation	155(F) utilized to 130(B)	H23	Radial sealing ring at the DE for flange types of construction, oil-tight up to 0.1 bar
Duty type	S1	R50	Larger terminal box
Direction of rotation	Bidirectional		
Frame material	Cast iron		
Data of anti condensation heating	-/-		
Coating (paint finish)	Standard paint finish		
Color, paint shade	RAL7030		
Motor protection	(A) without		
Method of cooling	IC411 - Self ventilated, surface cooled		
Forced ventilation motor details	- / -		
Weight in kg, without optional accessories	43 kg		
Rotor weight in kg	8,9 kg		
Moment of inertia	Rotor GD <sup>2</sup>	0.01055 kg m <sup>2</sup>	0.0422 kgf.m <sup>2</sup>

### Notes

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / nominal current

M<sub>K</sub>/M<sub>N</sub> = break down torque / nominal torque

M<sub>A</sub>/M<sub>N</sub> = locked rotor torque / nominal torque