



MLFB-Ordering data: 1LE7501-1CA13-5FA4

Frame size: 132S

Client order no.:

Order no.:

Offer no.:

Remarks:

Item no.:

Consignment no.:

Project:

U [V]±10%	Δ/Y	f [Hz]±5%	P [kW]	I [A]	n [1/min]	M [kgf.m]	M [Nm]	NOM. EFF at ... load [%] *			Power factor at ... load *			I _A /I _N	M _A /M _N	M _k /M _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I _A /I _N	T _f /T _N	T _B /T _N	
415	Δ	50	7.50	13.00	2925	2.5	24.5	88.6	88.6	88.6	0.90	0.87	0.79	7.0	2.4	3.4	IE2

Data subject to tolerance as per IS 12615 / IEC 60034-1

SF: 1.00

*sinusoidal feed

Environmental conditions : -20 °C to +50 °C / 1000.0 m

locked rotor withstand time (hot / cold) : 10.0 s / 15.0 s

Mechanical data				Terminal box		
Sound pressure level 50Hz 60Hz		75 dB(A)	80 dB(A)	Terminal box position		Top
Type of construction		IM B5 / IM 3001		Material of terminal box		Aluminium
Bearing DE NDE		6208 2ZC3	6208 2ZC3	Type of terminal box		TB1 H04
Type of bearing		Locating (fixed) bearing, NDE		Contact screw thread		M5
Lubricants		Esso Unirex N3		Max. cross-sectional area		16.0 mm²
Regreasing device		- / -		Cable diameter from ... to ...		11.0 mm - 21.0 mm
Grease nipple		- / -		Cable entry		2xM32x1,5
Bearing lifetime		50000 h		Cable gland		2 Plugs
Degree of protection		IP55				
External earthing terminal		Yes (standard)				
Vibration severity grade		A (Standard)				
Insulation		155(F) utilized to 130(B)				
Duty type		S1				
Direction of rotation		Bidirectional				
Frame material		Cast iron				
Data of anti condensation heating		-/-				
Coating (paint finish)		Standard paint finish				
Color, paint shade		RAL7030				
Motor protection		(A) without				
Method of cooling		IC411 - Self ventilated, surface cooled				
Forced ventilation motor details		- / -				
Weight in kg, without optional accessories		66 kg				
Rotor weight in kg		12,9 kg				
Moment of inertia	Rotor GD²	0.01593 kg m²	0.06372 kgf.m²			

Notes

I_A/I_N = locked rotor current / nominal current

M_k/M_N = break down torque / nominal torque

M_A/M_N = locked rotor torque / nominal torque